

01-06-06

ZFW

PTO/SB/21 (09-04)

Approved for use through 07/31/2006. OMB 0651-0031

U.S. Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

**TRANSMITTAL
FORM**

(to be used for all correspondence after initial filing)

Total Number of Pages in This Submission

2*

Application Number

10/664,274

Filing Date

September 16, 2003

First Named Inventor

Micael NILSSON

Art Unit

1724

Examiner Name

R. H. Spitzer

Attorney Docket Number

514862000800

ENCLOSURES (Check all that apply)☐ Fee Transmittal Form☐ Fee Attached☐ Amendment/Reply☐ After Final☐ Affidavits/declaration(s)☐ Extension of Time Request☐ Express Abandonment Request☐ Information Disclosure Statement☒ Certified Copy of Priority Document(s) (2 priority docs)☐ Reply to Missing Parts/Incomplete Application☐ Reply to Missing Parts under 37 CFR 1.52 or 1.53☐ Drawing(s)☐ Licensing-related Papers☐ Petition☐ Petition to Convert to a Provisional Application☐ Power of Attorney, Revocation Change of Correspondence Address☐ Terminal Disclaimer☐ Request for Refund☐ CD, Number of CD(s) _____☐ Landscape Table on CD☐ After Allowance Communication to TC☐ Appeal Communication to Board of Appeals and Interferences☐ Appeal Communication to TC (Appeal Notice, Brief, Reply Brief)☐ Proprietary Information☐ Status Letter☒ Other Enclosure(s) (please identify below):

RETURN RECEIPT POSTCARD

***DOES NOT INCLUDE PAGE COUNT OF PRIORITY DOCS**

Remarks

SIGNATURE OF APPLICANT, ATTORNEY, OR AGENT

Firm Name

MORRISON & FOERSTER LLP

(CUSTOMER NO. 20872)

Signature

Printed name

Otis Littlefield

Date

January 4, 2006

Reg. No.

48,751

I hereby certify that this correspondence is being deposited with the U.S. Postal Service as Express Mail, Airbill No.

EV 731 515 124 US, in an envelope addressed to: MS: ISSUE FEES, Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450, on the date shown below.

Dated: January 4, 2006

Signature:

(Lilia Olsen)

EV731515124US



I hereby certify that this correspondence is being deposited with the U.S. Postal Service as Express Mail, **Airbill No. EV 731 515 124 US**, in an envelope addressed to: **MS: ISSUE FEES**, Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450, on the date shown below.

Dated: January 4, 2006

Signature: 

(Dilla Olsen)

Docket No.: 514862000800
(PATENT)

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Patent Application of:
Mikael NILSSON

Application No.: 10/664,274

Confirmation No.: 3437

Filed: September 16, 2003

Art Unit: 1724

For: SCRUBBER

Examiner: R. H. Spitzer

CLAIM FOR PRIORITY AND SUBMISSION OF DOCUMENTS

MS: ISSUE FEES

Commissioner for Patents
P.O. Box 1450
Alexandria, VA 22313-1450

Dear Sir:

Applicant hereby claims priority under 35 U.S.C. 119 based on the following prior foreign application(s) filed in the following foreign country on the date indicated:

<u>Country</u>	<u>Application No.</u>	<u>Date</u>
SWEDEN	0202741-5	September 16, 2002
SWEDEN	0202905-6	October 2, 2002

In support of this claim, a certified copy of the said original foreign application is filed herewith.

Dated: January 4, 2006

Respectfully submitted,

By 

Otis Littlefield

Registration No.: 48,751
MORRISON & FOERSTER LLP
425 Market Street
San Francisco, California 94105-2482
(415) 268-6846

PRV

PATENT- OCH REGISTRERINGSVERKET

Patentavdelningen

Intyg Certificate

Härmed intygas att bifogade kopior överensstämmer med de handlingar som ursprungligen ingivits till Patent- och registreringsverket i nedannämnda ansökan.

This is to certify that the annexed is a true copy of the documents as originally filed with the Patent- and Registration Office in connection with the following patent application.

(71) Sökande Aerocrine AB, Solna SE
Applicant (s)

(21) Patentansökningsnummer 0202905-6
Patent application number

(86) Ingivningsdatum 2002-10-02
Date of filing

Stockholm, 2005-12-20

För Patent- och registreringsverket
For the Patent- and Registration Office


Hjördis Segerlund

Avgift
Fee 170:-

Scrubber

The present invention relates to a scrubber for eliminating a component from air flowing through the scrubber.

Technical background

Known scrubbers comprise a housing having at least one inlet hole and an outlet hole and comprising filtering material. A scrubber may for example be used in any equipment where for example NO-free air is needed, e.g. for calibration, as in an equipment for measuring the level of nitric oxide in air, especially exhalation air, or any other gas mixture. In such a case a test person inhales air through the scrubber so that NO will be filtered from the air. The air flow may for example be about 1-10 litre/second.

Preferably a return valve is positioned between the inlet/outlet of the equipment, through which inlet/outlet the test person inhales/exhales, and the outlet of the scrubber so that the exhaled air does not pass the scrubber but reaches any sensing portion of the equipment.

When taking a zero reference for the sensing portion of the equipment or making a function control, a small flow of component-free air, for example NO-free air, is used and taken between the outlet of the scrubber and the return valve. One problem with this is that the possibility exists that the zero reference will be mixed with a leakage back flow through the return valve. This would compromise the accuracy of the zero measurement.

This is of course true for any filtering of a component from air. Therefore, it is an object of the present invention to provide a scrubber, which safely makes sure that the zero reference flow actually comes from the scrubber and is identical to the component-free air inhaled by the test person.

Summary of the invention

10 This object is met by a scrubber according to claim 1.

An advantage with this solution is, in the case of a leakage or breakage of a return valve, the depth of the filtering material will still be large enough for filtering the air, making the system safe. This also gives the advantage that the return valve may be an ordinary mechanical one suitable for large flow rates, which is less expensive, instead of an electrically controlled valve needed for handling low flow rates.

20 Another problem with known scrubbers is that the outlet is designed for large flow rates, which means that there is a large "dead space" in the outlet with air that has been stagnant in this space and the zero reference or function control flow will have to go on for a long time before you may be sure that the air has flown through the scrubber.

30 According to an embodiment of the present invention this second outlet is smaller than the first outlet, whereby the "dead space" in the second outlet is minimal forming a very effective system where less air needs to flow through the scrubber and the system in order to make sure that a zero reference has been safely registered.

Preferably the scrubber is provided for filtering NO from air.

5 A problem with known NO-scrubbers is that they comprise carbon filters for the elimination of NO. However, these scrubbers are not suitable for long-term use. They lose their capability of eliminating NO quickly when exposed to humidity even at commonly existent ambient humidity levels. Another drawback is that they need to be
10 voluminous to be able to eliminate NO at high flows and concentrations commonly encountered in urban environments.

Therefore it is also an object of the present invention to provide a small scrubber, which is suitable for long-term
15 use. The solution to this is a scrubber comprising potassium permanganate KMnO_4 or potassium permanganate in combination with a suitable grade of carbon. An advantage with this material is that it binds NO and forms manganese dioxide. This retains its filtering capability in
20 moisturous environments, actually better than in dry environments.

Short description of the drawings

25 The present invention will be described showing an embodiment of a scrubber according to the present invention together with drawings, in which:

30 Fig. 1 illustrates a cross section view of an embodiment of a scrubber according to the present invention.

Fig. 2 illustrates the scrubber of Fig. 1 in a view showing an end side having inlet holes.

Fig. 3 illustrates the scrubber of Fig. 1 in a perspective view.

Detailed description of a preferred embodiment

5

The scrubber of the present invention comprises a housing 1 having at least one inlet hole 2, in the shown embodiment several small inlet holes 2 spread over an end side 3, and a first outlet hole 4 in the end side 5 opposite the inlet end side 3. Within the housing 1 is a filtering material 6 present.

Between the housing 1 and the filtering material 6 at the inlet holes 2 and the first outlet hole 4 is a particle filter 7 present to stop particles of the filtering material 6 from leaving the scrubber through the holes 2, 4.

The scrubber of the shown embodiment has a cylindrical wall 8 between the two end sides 3, 5 but of course other shapes are conceivable. At the wall 8 a second outlet hole 9 is present. Also this hole 9 is protected on the inside with a particle filter 7 to stop particles of the filtering material 6 from leaving the scrubber through the second hole 9. In the shown embodiment the air flowing through the filtering material 6 from the inlet holes 2 to the second outlet 9 passes via a channel 10.

The first outlet hole 4 is designed for a throughput of about 1-10 litres/second of air and the second outlet hole 9 is designed for a throughput of about 0,5-50 millilitres/second, preferably.

In order to make sure that the air leaving the second outlet hole 9 has passed a sufficient depth of the filtering material 6, there are not any inlet holes 2 in the inlet end side 3 in the vicinity of the second outlet hole 9. In such way the air must travel a depth in the filtering material 6, for example at least corresponding substantially to the depth for the air to travel between the inlet holes 2 and the first outlet hole 4, making sure that the component, for example NO, will be filtered from the air.

In order to make the air flow from the inlet holes 2 to the second outlet hole 9 and not from the first outlet hole 4 to the second outlet hole 9 a return valve 11 may be arranged in the first outlet hole 4 or outside in the extension of the outlet hole 4.

As a safety measure, in case of leakage in the return valve 11, the second outlet 9 should be provided at a distance from the first outlet valve 4 also. Thus the air must travel a depth in the filtering material 6 at least corresponding substantially to depth for the air to travel between the inlet holes 2 and the first outlet hole 4, making sure that the component, for example NO, will be filtered from the air.

The filtering material 6 is preferably potassium permanganate KMnO_4 or potassium permanganate in combination with a suitable grade of carbon in granular form if the component to be removed is NO. The granules may have the size $1/8$ - $1/128$ of an inch and preferably $1/32$ - $1/64$ of an inch. Preferably the air leaving the scrubber from any of the outlet holes 4, 9 has a content of NO less than 5 ppb, in general in urban environments.

The present invention is not limited to the shown and described embodiments but can be varied and amended within the scope of the attached claims.

Claims

1. A scrubber for eliminating a component from air
5 flowing through the scrubber, comprising a housing
(1) having at least one inlet hole (2) and an outlet
hole (4) and which is comprising filtering material
(6), **characterised in** that a second outlet hole (9)
is provided in the housing (1) at a position situated
10 at a distance from the first outlet hole (4) and any
inlet hole (2) so that the air leaving the second
outlet hole (9) will have passed at least through a
depth of the filtering material (6) substantially
corresponding to the depth of the filtering material
15 (6) for the air flowing from the inlet hole (2) to
the first outlet hole (4).
2. A scrubber according to claim 1, wherein the second
outlet hole (9) is intended for a smaller throughput
20 of air than the first outlet hole (4).
3. A scrubber according to claim 1 or 2, wherein several
inlet holes (2) are provided in the housing (1) in an
end side (3) opposite an end side (5) comprising the
first outlet hole (4).
25
4. A scrubber according to claim 1, 2 or 3, wherein the
second outlet hole (9) is provided at the wall (8) of
the housing (1) between the two end sides (3, 5).
30
5. A scrubber according to any one of the previous
claims, wherein no inlet holes are present in the end
side (5) comprising the first outlet hole (4) in the
vicinity of the second outlet hole (9) so that the

air will flow at least through a depth of the filtering material substantially corresponding to the depth of the filtering material (6) for the air flowing through the first outlet hole (4).

5

6. A scrubber according to any one of the previous claims, wherein a non-return valve (11) is provided in the first outlet hole (4).

10

7. A scrubber according to any one of the previous claims, wherein the scrubber is provided for filtering NO.

15

8. A scrubber according to claim 7, wherein the filter material (6) is potassium permanganate KMnO_4 or potassium permanganate in combination with a suitable grade of carbon.

20

9. A scrubber according to claim 7 or 8, wherein the scrubber eliminates NO to a level less than 5 ppb.

25

10. A scrubber according to any one of the previous claims, wherein a particle filter (7) is provided inside the housing (1) at least at the inlet holes (2) and at the first and second outlet holes (4, 9) in order to stop the filter material (6) to escape from the scrubber.

30

11. A scrubber according to any one of the previous claims, wherein the flow rate through the first outlet hole (4) is about 1-10 l/s and the flow rate through the second outlet hole (9) is about 0,5-50 ml/s.


12.A scrubber according to any one of the previous claims, wherein the size of the particles of the filtering material is in the range of $1/8$ - $1/128$ of an inch and preferably $1/32$ - $1/64$ of an inch.



Abstract

5 A scrubber for eliminating NO from air flowing through
the scrubber, comprising a housing (1) having at least
one inlet hole (2) and an outlet hole (4) and which is
comprising filtering material (6). A second outlet hole
10 (9) is provided in the housing (1) at a position
situated at a distance from the first outlet hole (4)
and any inlet hole (2) so that the air leaving the
second outlet hole (9) will have flown at least through
a depth of the filtering material (6) substantially
15 corresponding to the depth of the filtering material (6)
for the air flowing from the inlet hole (2) to the first
outlet hole (4).

1/2

Fig 1





**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.